



t +86-760-22343190
m +86 173 2816 2503
e sales@luna-lighting.cn
www.luna-lighting.com

Magnetic up-down light pendant light 10watts DC48V



LUNA Magnetic Track System is a new comprehensive and flexible system to design light in space.


48VDC low-voltage safe power supply, allowing customers to safely put their hands into the track to disassemble and assemble the lamps.

Customers pre-installed the track: Extruded aluminum housing slots, and then matched different surface lighting, spotlights, chandeliers, wall washer and other lamps according to the actual application scene. The light elements snap in place and connect automatically through the magic of magnets.

In addition, pre-configured corners complete the system to run up, around and across walls and ceilings.

Linear LED and accent fixtures, available in a variety of sizes, can be quickly replaced, removed or repositioned at any time according to the situation, without any tools, with artistic effects. Fun for customers to experience magnets and lights.

4 wires 2 circuits, also compatible with DALI and Bluetooth for dimming and color changing. (This function is under development).



Product model: LN-CMG-P30

Electrical

Power	10W
Input voltage	DC48V
Frequency	
Driver options	KEGU,Dadou
Dimming	on/off,0/1-10V,DALI,Mesh
Class	III SELV
Ambient temperature	0 - 40°C
Relative humidity	<85%

LED

LED brand options	CREE,OSRAM,PHILIPS
LED Qty	1
LED type	COB
C.C.T.	3000K,4000K,6000K
CRI	>80,>90
Lumen maintenance	LM80
SDCM	4

Optical

Beam angle °	24,36,60,90
Luminous flux (LED)* lm	1200
Lumen efficiency (LED)* lm/W	120
Luminous flux (Luminare)* lm	750
Lumen efficiency (Luminare)* lm/W	75

Material

Body & heatsink	Die-casting aluminum
Housing	ABS gear box
Optics	Optical PMMA
Surface treatment	Powder coated
Color options	Matt Black
IP grade	IP20

Installation

Location	Interior
Fixition	Magnetic track
Size mm	W30*H300mm
Cutout mm	N/A
Certificates	CE

On request

- different power, CRI, C.C.T..
- other LED Brands, CREE, OSRAM, SAMSUNG, Bridgelux, etc.
- other Drivers, OSRAM, PHILIPS, Meanwell, KEGU, Lifud, etc.
- dimming functions: TRIAC, 0/1-10V, DALI, Mesh, 2.4G
- emergency kit with specific duration.

*Due to the differences in test instruments and electronic components, the specific data may vary. Please confirm the specific parameters of the lamp before ordering to avoid misunderstanding. The luminous flux data and electrical data on the website will have +/-10% tolerance and measured at Tc 25°C indoors.

*Dimensions and specifications subject to alterations without notice.

Add: NO.16 Industrial 2nd Road, Caosan, Guzhen, Zhongshan, Guangdong, China . www.luna-lighting.com Email: sales@luna-lighting.cn Wechat: Luna_lighting

LUNA Mcfion Lighting Factory @ Copyright 2020