



t +86-760-22343190
m +86 173 2816 2503
e sales@luna-lighting.cn
www.luna-lighting.com

Magnetic linear folded light length 136mm 10watts DC48V

LUNA Magnetic Track System is a new comprehensive and flexible system to design light in space.

48VDC low-voltage safe power supply, allowing customers to safely put their hands into the track to disassemble and assemble the lamps.


Customers pre-installed the track: Extruded aluminum housing slots, and then matched different surface lighting, spotlights, chandeliers, wall washer and other lamps according to the actual application scene. The light elements snap in place and connect automatically through the magic of magnets.

Applications

architectural, commercial, exhibition areas, transit areas, corridors, shops, display windows, service areas, offices, staterooms, schools, halls, households, etc



©MCFION-LUNA



Product model: LN-CMGLINE-X-136

Electrical

Power	10W
Input voltage	DC48V
Frequency	50..60Hz
Driver options	KEGU,Dadou
Dimming	on/off,0/1-10V,DALI,Mesh
Class	III SELV
Ambient temperature	0 - 40°C
Relative humidity	<85%

LED

LED brand options	CREE,OSRAM,PHILIPS
LED Qty	5
LED type	SMD3030
C.C.T.	3000K,4000K,6000K
CRI	>80,>90
Lumen maintenance	LM80
SDCM	4

Optical

Beam angle °	15,24,36
Luminous flux (LED)* lm	1250
Lumen efficiency (LED)* lm/W	125
Luminous flux (Luminare)* lm	750
Lumen efficiency (Luminare)* lm/W	75

Material

Body & heatsink	Die-casting aluminum
Housing	ABS gear box
Optics	Optical PMMA
Surface treatment	Powder-Coated
Color options	Matt Black
IP grade	IP20

Installation

Location	Interior
Fixition	Magnetic track
Size mm	L270*W100*H35mm
Cutout mm	N/A
Certificates	CE

On request

- different power, CRI, C.C.T..

- other LED Brands, CREE, OSRAM, SAMSUNG, Bridgelux, etc.
- other Drivers, OSRAM, PHILIPS, Meanwell, KEGU, Lifud, etc.
- dimming functions: TRIAC, 0/1-10V, DALI, Mesh, 2.4G
- emergency kit with specific duration.

*Due to the differences in test instruments and electronic components, the specific data may vary. Please confirm the specific parameters of the lamp before ordering to avoid misunderstanding. The luminous flux data and electrical data on the website will have +/-10% tolerance and measured at Tc 25°C indoors.

*Dimensions and specifications subject to alterations without notice.

Add: NO.16 Industrial 2nd Road, Caosan, Guzhen, Zhongshan,
Guangdong, China . www.luna-lighting.com Email: sales@luna-lighting.cn Wechat: Luna_lighting

LUNA Mcfion Lighting Factory @ Copyright 2020