

t +86-760-22343190 m +86 173 2816 2503 e sales@luna-lighting.cn www.luna-lighting.com

## Magnetic square light length 220mm 30watts DC48V

LUNA Magnetic Track System is a new comprehensive and flexible system to design light in space.


48VDC low-voltage safe power supply, allowing customers to safely put their hands into the track to disassemble and assemble the lamps.

Customers pre-installed the track: Extruded aluminum housing slots, and then matched different surface lighting, spotlights, chandeliers, wall washer and other lamps according to the actual application scene. The light elements snap in place and connect automatically though the magic of magnets.

## **Applications**

architectural, commercial, exhibition areas, transit areas, corridors, shops, display windows, service areas, offices, staterooms, schools, halls, households, etc





## Product model: LN-CMG-TS30

## Electrical

Power 30W

Input voltage DC48V

Frequency

Driver options KEGU, Dadou

Dimming on/off,0/1-10V,DALI,Mesh

Class III SELV

Ambient temperature 0 − 40°C

Relative humidity <85%

**LED** 

LED brand options CREE,OSRAM,PHILIPS

LED Qty 30

LED type SMD3030

C.C.T. **3000K,4000K,6000K** 

CRI >80,>90

Lumen maintenance LM80

SDCM 4

Optical

Beam angle ° 15,36,60

Luminous flux (LED)\* lm 3750

Lumen efficiency (LED)\* lm/W 125

Luminous flux (Luminare)\* lm 2250

Lumen efficiency (Luminare)\* Im/W 75

Material

Housing ABS gear box

Optics PAAM

Surface treament Powder coated

Color options Matt Black

IP grade IP20

Installation

Location Interior

Fixition Magnetic track

Size mm **L220\*W137\*D47mm** 

Cutout mm N/A

Certificates CE

On request

- different power, CRI, C.C.T..

- other LED Brands, CREE, OSRAM, SAMSUNG, Bridgelux, etc.
- other Drivers, OSRAM, PHILIPS, Meanwell, KEGU, Lifud, etc.
- dimming functions: TRIAC, 0/1-10V, DALI, Mesh, 2.4G
- emergency kit with specific duration.

\*Due to the differences in test instruments and electronic components, the specific data may vary. Please confirm the specific parameters of the lamp before ordering to avoid misunderstanding. The luminous flux data and electrical data on the website will have +/-10% tolerance and measured at Tc 25°C indoors.

\*Dimensions and specifications subject to alterations without notice.

Add: NO.16 Industrial 2nd Road, Caosan, Guzhen, Zhongshan, Guangdong, China . www.luna-lighting.com Email: sales@luna-lighting.cn Wechat: Luna\_lighting

LUNA Mcfion Lighting Factory @ Copyright 2020