

t +86-760-22343190 m +86 173 2816 2503 e sales@luna-lighting.cn www.luna-lighting.com

Embedded linear light mini 12cells 24watts


The lamp shell is made of efficient aluminum die-casting aluminum material, with a slim black housing and a sharp square frame design, giving people a sense of modern and fashion.

This product uses CREE/OSRAM SMD high power LED chip and high quality isolated circuit power supply driver, high heat efficiency die-casting aluminum housing, colorfast sufrace treament, corrosion resistance, ensuring realiable quality.

This series of products offer various optical effect options: 15/30/45 spot angles, wall washer effect, and all come with anti-glare design, a inheritance of LUNA's professional commercial lighting ideas.

By rendering high CRI, gentle, warm and satisfied lighting effects, this product line can be used in stores, shopping centers, exhibition halls, offices, etc.





Product model: LN-CROLINE-S12

Electrical

Power 24W Max. 5-24W optional

Input voltage AC220-240V

Frequency 50..60Hz

Driver options OSRAM, PHILIPS, KEGU, LIFUD, Anxiong

Dimming on/off, TRAIC, 0/1–10V, DALI

Class III SELV

Ambient temperature O - 40°C

Relative humidity <85%

LED

LED brand options CREE, OSRAM, Samsung

LED Qty 12

LED type SMD3030

C.C.T. **3000K,4000K,6000K**

CRI **>80, >90**

Lumen maintenance LM80

SDCM 4

Optical

Beam angle ° 30,60,

Luminous flux (LED)* lm 2880

Lumen efficiency (LED)* lm/W 120

Luminous flux (Luminare)* lm 1200

Lumen efficiency (Luminare)* lm/W 50

Material

Body & heatsink Die-casting aluminum

Housing Die-casting aluminum

Optics PMMA

Surface treament Powder coated

Color options Matt White

IP grade IP20

Installation

Location Interior

Fixition Recessed

Size mm L204*W32*H40mm

Cutout mm L200*27mm

Certificates CE

On request

- different power, CRI, C.C.T..
- other LED Brands, CREE, OSRAM, SAMSUNG, Bridgelux, etc.
- other Drivers, OSRAM, PHILIPS, Meanwell, KEGU, Lifud, etc.
- dimming functions: TRIAC, 0/1-10V, DALI, Mesh, 2.4G
- emergency kit with specific duration.

*Due to the differences in test instruments and electronic components, the specific data may vary. Please confirm the specific parameters of the lamp before ordering to avoid misunderstanding. The luminous flux data and electrical data on the website will have +/-10% tolerance and measured at Tc 25°C indoors.

*Dimensions and specifications subject to alterations without notice.

Add: NO.16 Industrial 2nd Road, Caosan, Guzhen, Zhongshan, Guangdong, China . www.luna-lighting.com Email: sales@luna-lighting.cn Wechat: Luna_lighting

LUNA Mcfion Lighting Factory @ Copyright 2020