

t +86-760-22343190 m +86 173 2816 2503 e sales@luna-lighting.cn www.luna-lighting.com

Square Stretch adjustable Recessed spotlight-FS1

Recessed Telescopic spotlights.


The lamp shell is made of efficient aluminum die-casting aluminum material, , the surface is white spray treatment, fadeless, corrosion resistant, minimalist appearance design, large light range, no dead Angle of light beam 360° rotating irradiation goods expansion, horizontal rotation, expansion at will.

This product uses CREE/OSRAM SMD high-power LED chip and high quality isolation circuit power supply drive to ensure reliable quality.

The series offers a variety of optical effects:12/24/38/corner, wall wash effect, anti-glare design, LUNA LED strobe control to invisible category, making the light more delicate and even, making the visual experience of human eyes more soft and natural, making families comfortable and at ease.

This series of products can be used in shopping malls, shopping centers, exhibition halls, offices and other places, with high CRI, soft, warm, comfortable lighting effects.





Product model: LN-CRXLS-FS1

Electrical

Power 5-12W

Input voltage AC220-240V

Frequency 50..60Hz

Driver options OSRAM, PHILIPS, KEGU, LIFUD, Anxiong

Dimming on/off, TRAIC, O/1–10V, DALI, Mesh

Class III SELV

Ambient temperature 0 − 40°C

Relative humidity <85%

LED

LED brand options CREE, OSRAM, PHILIPS

LED Qty 1

LED type COB

C.C.T. **3000K,4000K,6000K**

CRI >80, >90

Lumen maintenance LM80

SDCM 4

Optical

Beam angle ° 12,24,38

Luminous flux (LED)* lm 1440

Lumen efficiency (LED)* lm/W 120

Luminous flux (Luminare)* lm 900

Lumen efficiency (Luminare)* Im/W 75

Material

Body & heatsink Die-casting aluminum

Housing Die-casting aluminum

Optics PMMA

Surface treament Powder coatedv

Color options Sanded White

IP grade IP20

Installation

Location Interior

Fixition Ceiling Recessed

Size mm L100*W100*H120mm

Cutout mm Φ 90mm

Certificates CE

On request

- different power, CRI, C.C.T..

- other LED Brands, CREE, OSRAM, SAMSUNG, Bridgelux, etc.
- other Drivers, OSRAM, PHILIPS, Meanwell, KEGU, Lifud, etc.
- dimming functions: TRIAC, 0/1-10V, DALI, Mesh, 2.4G
- emergency kit with specific duration.

*Due to the differences in test instruments and electronic components, the specific data may vary. Please confirm the specific parameters of the lamp before ordering to avoid misunderstanding. The luminous flux data and electrical data on the website will have +/-10% tolerance and measured at Tc 25°C indoors.

*Dimensions and specifications subject to alterations without notice.

Add: NO.16 Industrial 2nd Road, Caosan, Guzhen, Zhongshan, Guangdong, China . www.luna-lighting.com Email: sales@luna-lighting.cn Wechat: Luna_lighting

LUNA Mcfion Lighting Factory @ Copyright 2020